



# PRODUCT SPECIFICATIONS

MODULAR METAL FABRICATORS INC.

## Sleeve with Damper



### DESCRIPTION

Sleeves with damper are fabricated from galvanized steel, with crimp and bead one end, bead and raw the other end. Sleeves are diameter plus 1" for overall length. Damper is factory installed by using 1 1/2" or 2" standoff, 3/8" continuous square rod, and is attached with 2 rod clips and 3/8" nylon bushing on each end.

#### 1 1/2 INCH STANDOFF

PART NO.	SLEEVE	DAMPER	STAND OFF	A	B	BUSHINGS	ROD
DMSJM0506	24 GA	18GA	1.5"	05"	06"	NYLON	38"
DMSJM0607	24 GA	18GA	1.5"	06"	07"	NYLON	38"
DMSJM0708	24 GA	18GA	1.5"	07"	08"	NYLON	38"
DMSJM0809	24 GA	18GA	1.5"	08"	09"	NYLON	38"
DMSJM0910	24 GA	18GA	1.5"	09"	10"	NYLON	38"
DMSJM1011	24 GA	18GA	1.5"	10"	12"	NYLON	38"
DMSJM1213	24 GA	18GA	1.5"	12"	14"	NYLON	38"
DMSJM1415	24 GA	18GA	1.5"	14"	16"	NYLON	38"
DMSJM1617	24 GA	18GA	1.5"	16"	18"	NYLON	38"
DMSJM1819	24 GA	18GA	1.5"	18"	20"	NYLON	38"
DMSJM2021	24 GA	18GA	1.5"	20"	21"	NYLON	38"

#### 2 INCH STANDOFF

PART NO.	SLEEVE	DAMPER	STAND OFF	A	B	BUSHINGS	ROD
DMSJM05062	24 GA	18GA	2"	05"	06"	NYLON	38"
DMSJM06072	24 GA	18GA	2"	06"	07"	NYLON	38"
DMSJM07082	24 GA	18GA	2"	07"	08"	NYLON	38"
DMSJM08092	24 GA	18GA	2"	08"	09"	NYLON	38"
DMSJM09102	24 GA	18GA	2"	09"	10"	NYLON	38"
DMSJM10112	24 GA	18GA	2"	10"	12"	NYLON	38"
DMSJM12132	24 GA	18GA	2"	12"	14"	NYLON	38"
DMSJM14152	24 GA	18GA	2"	14"	16"	NYLON	38"
DMSJM16172	24 GA	18GA	2"	16"	18"	NYLON	38"
DMSJM18192	24 GA	18GA	2"	18"	20"	NYLON	38"
DMSJM20212	24 GA	18GA	2"	20"	21"	NYLON	38"