

## Introducing a new innovation: M-Guard Flexible Duct with Owens Corning ™ EcoTouch® Insulation

Modular Metal M-Guard Flexible Air Duct is an UL 181 Class air duct that is tested & listed by Underwriters Laboratories.

Underwriters Laboratories' rigorous testing and long-term follow up services ensure that <u>all</u> Modular Metal air duct products are in compliance with all smoke, flame, mold growth, and humidity standards for the HVAC Industry.

- Complies with NFPA Standards 90A & 90B.
- Manufactured with tear resistant reinforced metalized polyester or black polyester vapor barriers
- Strong air-tight polyester, black inner core laminated and encapsulated with industry leading galvanized corrosion resistant steel wire helix.
- Manufactured in R-4.2, R-6, & R-8.
- Standard lengths: 25ft with raw both ends as well as 6ft with collars both ends.
- 5 year limited warranty.
- Available in cartons as well as poly bags.
- Thick blanket of Owens Corning™ USDA Bio-based Formaldehyde Free\* EcoTouch® Insulation.
- Owens Corning™ EcoTouch® Insulation is Certified by Scientific Certification Systems to contain a minimum of 57% recycled content.
- Owens Corning™ EcoTouch® Insulation is certified to meet indoor air quality standards under the stringent GreenGuard Indoor Air Quality Certification Program, and the GreenGuard Children & Schools Certification Program.







INSULATION ATTRIBUTES	PINK	WHITE
USDA Biopreferred	YES	NO
Biobased Binder	YES	NO
Formaldehyde Free	YES	YES
Recycled Content	57%	25%
UL Enviornment	YES	NO









**Union Made** 



\* Applies to insulation componets only

Scientific Certification Systems (SCS) provides independent verification of recycled content in building materials and verifies recycled content claims made by manufacturers. For more information, visit www.scscertifled.com